



## PRODUCT SPECIFICATIONS:

- Product material Acrylix<sup>TM</sup> surface with fiberglass composite reinforcement.
- Certified to meet CSA B45.5/IAPMO Z124 Standard.
- Product has a Class B fire rating as determined by ASTM E-84 test method.
- Reinforced & slip resistant floor.
- Integral 1" [25mm] nailing flange.
- Door Opening: W-38 1/2" [978mm] x H-68" [1727mm]
- All dimensions +/- 1/2" [12.8mm]
- Clarion Bathware reserves the right to change design and/or dimensions.
- Dimensions are the same for RE, MP, and all other versions of this model.

CENTER DRAIN

42"[1067mm] Shower w/8" [203mm] Threshold & Molded Soap Ledge

## **4242SDX**

42" [1067mm] Shower w/ 8" [203mm] Threshold, Molded Soap Ledges & Center Drain

BATHWARE
44 Amsler Ave.
Shippenville, PA 16254

Phone: (814) 226-5374 Toll Free: (800) 576-9228 Fax: (814) 226-0730 www.clarionbathware.com

 Signatures For Approval:
 Date:
 Dwg. #

 Customer:
 4843SDX-CUT

 Arch./Engr:
 Dwg. By: CAL

 Job Name:
 DATE: 4/27/2021

## \*\*\* IMPORTANT NOTICE \*\*\*