Collection:Phineas

Installation manual for:

LD7012BR W36"\*H8.4"\*E5.8"L4

## Installation instructions:

- l. Black wire from ceiling(junction box) attaches to "L"wire from the fixture.
- 2. White wire from ceiling(junction box) attaches to "N"wire from the fixture.
- 3. "E" wire from the fixture is attaced to the mounting bracket and an additional "E" wire from the mounting bracket must be secured to the junction box.
- 4.Secure mounting bracket to the junction box.

  5.Insert screws (P2) in side of top unit the mounting bracket(P1).
- screw (P3) 6.Lock the lamp body on the mounting bracket (P1) on the wall with a flat head

7.Hang Crystal(P11) 8.Install E12 light source.(Bulbs not supplied)

The end!

## **PARTS LIST**

(LA.53"*W4.33"*H0.59")  Mounting bracket screw  Flat head Screw  Quare box (LA.8"*W4.8"*H0.8")  Double head tube (200.37"*L3.03")  Square tube (20.37"*L3.03")  Cylindrical iron (40.55"*H0.31")  Anti-edge light cup (401.57"*H1.57")  Anti-edge light cup (501.57"*H1.57")  E12 card type full tooth lamp head Flat iron frame frame flat iron flat iron frame flat iron flat ir
--

<sup>&</sup>quot;L" = Hot wire
"N" = Neutral wire
"E" = Ground wire