


**IMPORTANT  
TURN OFF THE POWER AT THE MAIN FUSE  
OR CIRCUIT BREAKER BOX  
BEFORE STARTING INSTALLATION**

**Carefully unpack and identify all parts before assembly. Bulb is not included.**

1. Slip candle cover tube onto sockets.
2. Install light bulb (Not Included). See relamping label located at socket area for type and maximum allowed wattage.
3. Screw center pipe onto center body. Note correct position of center pipe as shown in illustration.
4. Slip the top cover, and rubber washer through the installed center pipe. Lock them all together by fastening with finial.
5. Electrical installation onto post: If you are replacing an existing fixture, disconnect and remove the old fixture.
  - A) Slip post cup over post. Mark position of holes in post cup on post.
  - B) Remove post cup and expose the supply wiring from above post. Drill 1/8" (3mm) diameter pilot holes in post at places where marked.
  - C) Make wire connections. (wire connectors not provided). Refer to chart below for correct connections. Wire supply wires to fixture wires accordingly.

Connect Black Fixture Wire to:	Connect White Fixture Wire to:
Black Supply Wire or *Parallel cord (round & smooth)	White Supply Wire or *Parallel cord (square & ridged)
Clear, Brown, Gold or Black without tracer Insulated wire (other than green) with copper conductor	Clear, Brown, Gold or Black with tracer Insulated wire (other than green) with silver conductor

\*Note: When parallel wire (SPT 1 & SPT2) is used. One wire is square shaped or ridged and the other wire will be round in shape or smooth. (See Illustration)



- D) Connect ground wire from supply source to fixture ground wire with connector. Never connect ground wire to black or white power supply wires. Carefully place wires inside post.
- E) Slip post cup onto post. Align holes in post cup with holes in post. Attach post cup to post with sheet metal screws.