

SOLID BRASS FINIAL, POLISHED AND CLEAR LACQUERED.

CAST ALUMINUM CAP.

CAST ALUMINUM HEX ROOF SECURED TO CAGE WITH (2) 8-32 BRASS THUMBSCREWS. TO RELAMP, REMOVE BOTH THUMBSCREWS.

7 5/8" ACROSS POINTS

6 CLEAR GLASS (CG) CAGE PANELS SECURE WITH 1 PC. CLEAR POLYCARBONATE U.V. STABILIZED HEX CLIP. OTHER PANELS AVAILABLE—CONTACT FACTORY.

CAST ALUMINUM HEX CAGE WITH FROG BOTTOM.

PORCELAIN MEDIUM BASE SOCKET W/ANODIZED ALUMINUM COVER. 60 WATTS MAX. (LAMP NOT SUPPLIED).

BRASS ANODIZED ALUMINUM SLEEVE.

CAST ALUMINUM PIPE FITTER WITH (2) 1/4-20 S.ST'L. SET SCREWS TO SECURE FIXTURE TO GARDEN PIPE.

1/2" NPT PIPE THREADED ONE END. (PIPE MUST BE ORDERED SEPARATELY).

ACCESSORY PIPE	AVAILABLE NUMBERS
6390	12" LONG
6394	20" LONG
6393	30" LONG

LANTERN WILL BE PREWIRED AND TESTED. ELECTRICAL COMPONENTS ARE U.L. LISTED. ALL MOUNTING HARDWARE SUPPLIED.

HEIGHT	15 1/8"
WIDTH	7 5/8"
PROJECTION	
TOP TO OUTLET	

Drawing for illustration only — scale approximate

