



CAST ALUMINUM FINIAL.

CAST ALUMINUM HEX ROOF.

CAST ALUMINUM HEX CAGE W/FROG BOTTOM SECURED TO ROOF WITH (2) 8-32 BRASS THUMBSCREWS. TO RELAMP, REMOVE BOTH THUMBSCREWS.

6 (CBG) CLEAR BEVELED GLASS CAGE PANELS SECURED WITH CLIPS AND SCREWS. OTHER PANELS AVAILABLE—CONTACT FACTORY.

3 LIGHT CANDLE CLUSTER.
3 CANDELABRA SOCKETS
WITH PAINTED METAL COVERS.
2 PC. PAINTED CLUSTER
BODY (LAMPS NOT SUPPLIED)
25 WATT MAX. PER SOCKET.

PAINTED ALUMINUM SLEEVE.

CAST ALUMINUM SCROLL BRACKET ARM.

CAST ALUMINUM KNOB.

LANTERN IS PREWIRED AND TESTED. ELECTRICAL COMPONENTS ARE U.L. LISTED. MOUNTING HARDWARE IS SUPPLIED.

HEIGHT	27 5/8"
WIDTH	10 1/8"
PROJECTION	12 1/2"
TOP TO OUTLET	22 1/2"

Drawing for illustration only - scale approximate



"STURBRIDGE"
12400 SERIES
WALL BRACKET
LANTERN

SCALE: DATE: DWG BY: DWG. NO. 1=4 01/18/05 JEK B12410