



LANTERN CONSISTS OF:

CAST ALUMINUM REMOVABLE ROOF ASSEMBLY (LOOP, ROOF CAP, AND ROOF) FOR EASY RELAMPING AND REMOVAL OF CAGE PANELS. CAST ALUMINUM TOP AND BOTTOM CAGE FRAMES. CAST ALUMINUM REAR WALLPLATE. BOTTOM CAGE FRAME IS OPEN FOR ADDED DOWNLIGHT. TWO FRONT AND TWO REAR CAGE LEGS ARE ALUMINUM EXTRUSIONS WITH CHANNELS FOR HOLDING THE CAGE PANELS. THREE CLEAR SEEDED ACRYLIC (CSA) PANELS SHOWN (OTHERS AVAILABLE). THREE CANDELABRA PHENOLIC SOCKETS FOR 25 WATTS MAX. EACH. PAINTED SLEEVES HIDE SOCKETS. CURVED BRACKETS AND CHECK RINGS WILL HAVE THE SAME FINISH AS LANTERN. LANTERN WILL BE PREWIRED AND TESTED. ALL ELECTRICAL COMPONENTS ARE U.L. LISTED. ALL MOUNTING HARDWARE IS SUPPLIED.

Drawing for illustration only - scale approximate

HEIGHT	23"	APPROVAL SIGNATURE:
WIDTH	10 1/4"	FINISH: _____
PROJECTION	9 1/4"	PANELS: _____
TOP TO OUTLET	16"	OPTIONS: _____

Hanover
LANTERN

425 E. MIDDLE ST. HANOVER PA 17331
PH: (717) 632-6464 - FAX: (717) 969-2930

SCALE: 1=4 DATE: 06/30/05 DWG BY: KWF

TITLE:	"CAPE COD" 25400 SERIES WALL MOUNT LANTERN
DWG. NO.	B25409