

CAST ALUMINUM SQUARE ROOF ATTACHES TO CAGE WITH TWO BLACK OXIDE BRASS THUMBSCREWS. TO RELAMP, REMOVE THUMBSCREWS.

- 9 1/8" SQUARE

CAST ALUMINUM SQUARE CAGE ASSEMBLY WITH FROG BOTTOM.

FOUR OPALESCENT HONEY GLASS (OHG) CAGE PANELS SECURED WITH CLIPS AND SCREWS. OTHER PANELS AVAILABLE—CONTACT FACTORY.

PORCELAIN MEDIUM BASE SOCKET WITH PAINTED ALUMINUM SLEEVE. 40 WATTS. MAX. LAMP NOT SUPPLIED.

PAINTED ALUMINUM SLEEVE.

CAST ALUMINUM POST FITTER SLIPS OVER 3" O.D. POST OR TENON. (POST MUST BE ORDERED SEPARATELY).

- THREE 1/4-20 S.ST'L. SET SCREWS SECURE LANTERN TO POST OR TENON.

E.P.A. = 0.35 (EFFECTED PROJECTED AREA). LANTERN WILL BE PREWIRED AND TESTED. ALL ELECTRICAL COMPONENTS ARE U.L. LISTED. ALL MOUNTING HARDWARE IS SUPPLIED.

HEIGHT	13 1/2"
WIDTH	9 1/8"
PROJECTION	xxxx
TOP TO OUTLET	xxxx