TURNED ALUMINUM BALL FINIAL. SPUN ALUMINUM TOP CAP AND NECK. SPUN PAINTED ALUMINUM OR SPUN COPPER ROOF SECURES TO CAST ALUMINUM ROOF RING WITH 6 S.ST'L. SCREWS. CAST ALUMINUM ROOF RING SECURES TO CAGE WITH 2 BRASS BLACK OXIDE THUMBSCREWS. TO RELAMP, REMOVE THUMBSCREWS. — 11 7/8" DIA. 6 CLEAR BEVELED GLASS (CBG) 22 1/4" CAGE PANELS SECURE TO CAGÉ WITH CLIPS AND SCREWS. (OTHER PANELS AVAILABLE—CONTACT FACTORY) 3 LIGHT CANDLE CLUSTER. 3 CANDELABRA SOCKETS W/PAINTED METAL COVERS. 2 PC. PAINTED DIE CAST CLUSTER BODY. 25 WATTS MAX PER SOCKET. (LAMP NOT SUPPLIED). CAST ALUMINUM HEX CAGE WITH FROG BOTTOM. CAST ALUMINUM POST FITTER SLIPS OVER 3" O.D. POST OR TENON. (POST MUST BE ORDERED SEPARATELY). (3) 1/4-20 S.ST'L. SET SCREWS SECURE LANTERN TO POST OR TENON. 3" DIA. -

LANTERN WILL BE PREWIRED AND TESTED. ALL ELECTRICAL COMPONENTS ARE U.L. LISTED. ALL MOUNTING HARDWARE SUPPLIED.

E.P.A.: 0.93 (EFFECTIVE PROJECTED AREA)

HEIGHT	22 1/4"
WIDTH	11 7/8" DIA.
PROJECTION	
TOP TO OUTLET	

| Comparing for illustration only - scale approximate | Comparing for illustration only - scale approx