



TURNED ALUMINUM BALL FINIAL.

SPUN ALUMINUM TOP CAP AND NECK.

SPUN PAINTED ALUMINUM OR SPUN COPPER ROOF SECURES TO CAST ALUMINUM ROOF RING WITH 6 S.ST'L. SCREWS.

CAST ALUMINUM ROOF RING SECURES TO CAGE WITH 2 BRASS THUMBSCREWS. TO RELAMP, REMOVE THUMBSCREWS.

14 7/8" DIA.

31"

6 CLEAR BEVELED GLASS (CBG) CAGE PANELS SECURE TO CAGE WITH CLIPS AND SCREWS. (OTHER PANELS AVAILABLE—CONTACT FACTORY)

4 LIGHT CANDLE CLUSTER. 4 CANDELABRA SOCKETS W/PAINTED METAL COVERS. 2 PC. PAINTED DIE CAST CLUSTER BODY. 25 WATTS MAX PER SOCKET. (LAMP NOT SUPPLIED).

CAST ALUMINUM HEX CAGE WITH FROG BOTTOM.

CAST ALUMINUM POST FITTER SLIPS OVER 3" O.D. POST OR TENON. (POST MUST BE ORDERED SEPARATELY).

(3) 1/4-20 S.ST'L. SET SCREWS SECURE LANTERN TO POST OR TENON.

3" DIA.

LANTERN WILL BE PREWIRED AND TESTED.
 ALL ELECTRICAL COMPONENTS ARE U.L. LISTED.
 ALL MOUNTING HARDWARE SUPPLIED.
 E.P.A.: 1.40 (EFFECTIVE PROJECTED AREA)

HEIGHT	31"
WIDTH	14 7/8"
PROJECTION	
TOP TO OUTLET	

Drawing for illustration only — scale approximate

		TITLE:	
		"SOUTH BEND" 51600 SERIES POST TOP LANTERN	
<small>425 E. MIDDLE ST. HANOVER, PA 17331 PH: (717) 632-9464 - FAX: (717) 699-2930</small>		SCALE:	DATE:
1=4	12/13/04	DWG BY:	DWG. NO.
		ATV	B51630