

STAINLESS STEEL DRIVE PIN TO LOCK LANTERN TO ARM WITH (6) 1/4-20 STAINLESS STEEL SET SCREWS TO LEVEL AND SECURE LANTERN TO ARM.

TURNED ALUMINUM FINIAL.

SPUN ALUMINUM ROOF CAP.

CAST ALUMINUM ROOF NECK.

PAINTED PIPE NIPPLE.

CAST ALUMINUM SQUARE ROOF SECURES TO CAGE WITH 2 BRASS THUMBSCREWS. TO RELAMP, REMOVE THUMBSCREWS.

- 4 CLEAR BEVELED GLASS (CBG)
  PANELS SECURED WITH CLIPS
  AND SCREWS. OTHER PANELS
  AVAILABLE—CONTACT FACTORY.
- 4 LIGHT CANDLE CLUSTER.
  4 CANDELABRA SOCKETS WITH
  PAINTED METAL SLEEVES AND
  PAINTED CLUSTER BODY. 25
  WATTS MAXIMUM PER SOCKET.
  (LAMPS NOT SUPPLIED).

CAST ALUMINUM SQUARE CAGE WITH DECORATIVE LOOPS.

EXTRUDED ALUMINUM BENT BRACKET ARM WELDED TO POST FITTER.

CAST ALUMINUM POST FITTER SLIPS OVER 3" DIA. POST OR TENON. (POST MUST BE ORDERED SEPARATELY).

(6) 5/16-18 STAINLESS STEEL SET SCREWS SECURE LANTERN TO POST OR TENON.

LANTERN WILL BE PREWIRED AND TESTED.
ALL ELECTRICAL COMPONENTS ARE U.L. LISTED.
ALL MOUNTING HARDWARE IS SUPPLIED.

HEIGHT	28"
WIDTH	11 1/4"
PROJECTION	xxxx
TOP TO OUTLET	xxxx

Drawing for illustration only — scale approximate



JEFFERSON Signature 5700 SERIES POST TOP LANTERN

1=4 03/07/05 RSN

B5739