

DIE CAST ALUMINUM LOOP.


2 PC. CAST ALUMINUM BRACKET ARM AND WALLPLATE.

CAST ALUMINUM SQUARE ROOF SECURES TO CAGE WITH 8-32 BRASS THUMBSCREWS. TO RELAMP, REMOVE THUMBSCREWS.

INVERTED PORCELAIN MEDIUM BASE SOCKET W/PAINTED METAL COVER, 60 WATTS MAX. (LAMP NOT SUPPLIED).

-4 (CBG) CLEAR BEVELED GLASS CAGE PANELS SECURED W/CLIPS AND SCREWS. OTHER PANELS AVAILABLE— CONTACT FACTORY.

CAST ALUMINUM 4 PC. CAGE FRAME SECURELY WELDED TOGETHER TO FORM A SINGLE UNIT.



LANTERN WILL BE PREWIRED AND TESTED. ALL ELECTRICAL COMPONENTS ARE UL. LISTED. MOUNTING HARDWARE SUPPLIED.

HEIGHT	15"
WIDTH	6 7/8"
PROJECTION	9 7/8"
TOP TO OUTLET	4 3/4"

Drawing for illustration only - scale approximate



"ABINGTON"
8000 SERIES
WALL BRACKET
LANTERN

SCALE: DATE: DWG BY: DWG, NO. B8012RM