

DIE CAST ALUMINUM LOOP.

CAST ALUMINUM SQUARE ROOF SECURES TO CAGE WITH 8-32 BRASS THUMBSCREWS. TO RELAMP, REMOVE THUMBSCREWS.

6 7/8" SQUARE

4 (CSA) CLEAR SEEDED ACRYLIC CAGE PANELS SECURED W/CLIPS AND SCREWS. OTHER PANELS AVAILABLE—CONTACT FACTORY.

PORCELAIN MEDIUM BASE SOCKET W/PAINTED ALUMINUM COVER, 40 WATTS MAX. (LAMP NOT SUPPLIED). CAST ALUMINUM 4 PC. CAGE FRAME SECURELY WELDED TOGETHER TO FORM A SINGLE UNIT WITH FROG BOTTOM.

PAINTED ALUMINUM SLEEVE.

CAST ALUMINUM POST FITTER SLIPS OVER 3" O.D. POST OR TENON. (POST MUST BE ORDERED SEPARATELY).

(3) 1/4-20 S.ST'L. SET SCREWS SECURE LANTERN TO POST OR TENON.

Drawing for illustration only - scale approximate

LANTERN WILL BE PREWIRED AND TESTED.
ALL ELECTRICAL COMPONENTS ARE U.L. LISTED.
ALL MOUNTING HARDWARE IS SUPPLIED.

						TITLE: "ABINGTON"
HEIGHT	17 7/8"	APPROVAL SIGNATURE:		Hanc	<b>ver</b>	8000 SERIES
WIDTH	6 7/8"		<b>=</b> =	425 E. MIDDLE ST. HA		POST MOUNT
PROJECTION		FINISH:	SCALE:	: PH: (717) 632-6464 - F	AX: (717) 969-2930 DWG BY:	LANTERN DWG. NO.
TOP TO OUTLET		OPTIONS:		01/24/05		B8033