

DIE CAST ALUMINUM LOOP.

CAST ALUMINUM SQUARE ROOF SECURES TO CAGE WITH 2 BRASS THUMBSCREWS. TO RELAMP, REMOVE THUMBSCREWS.

4 CLEAR SEEDED ACRYLIC (CSA)
CAGE PANELS SECURED WITH CLIPS
AND SCREWS. OTHER PANELS
AVAILABLE—CONTACT FACTORY.

— 10" SQUARE

3 LIGHT CANDELABRA CLUSTER.
3 CANDELABRA SOCKETS WITH
PAINTED METAL COVERS. 25 WATTS
MAX. PER SOCKET. (LAMPS NOT
SUPPLIED).

CAST ALUMINUM 4 PC. CAGE FRAME SECURELY WELDED TOGETHER TO FORM A SINGLE UNIT WITH CAST ALUMINUM FROG BOTTOM.

- PAINTED ALUMINUM SLEEVE.

CAST ALUMINUM POST FITTER SLIPS OVER 3" DIA. POST OR TENON. POST MUST BE ORDERED SEPARATELY.

3 S.ST'L. SET SCREWS SECURE LANTERN TO POST OR TENON.

E.P.A.: 1.0 EFFECTED PROJECTED AREA

LANTERN WILL BE PREWIRED AND TESTED.

ALL ELECTRICAL COMPONENTS ARE UL. LISTED.

MOUNTING HARDWARE IS SUPPLIED. Drawing for illustration

Drawing for illustration only — scale approximate TITLE!'ABINGTON" APPROVAL SIGNATURE: HEIGHT 24" 8100 SERIES POST MOUNT 10" WIDTH 425 E. MIDDLE ST. HANOVER PA 17331 PH: (717) 632-6464 - FAX: (717) 969-2930 <u>LANTERN</u> FINISH: PROJECTION SCALE: DWG BY: DATE: DWG. NO. PANELS: B8133 01/25/05 RSN TOP TO OUTLET OPTIONS: