

DIE-CAST ALUMINUM LOOP.

CAST ALUMINUM SQUARE ROOF SECURES TO CAGE ASSEMBLY WITH (2) 8-32 BRASS THUMBSCREWS. TO RELAMP, REMOVE THUMBSCREWS.


10" SQUARE

4 PC. CAST ALUMINUM CAGE FRAME SECURELY WELDED TOGETHER TO FORM A SINGLE UNIT.

4 CLEAR SEEDED ACRYLIC (CSA) PANELS SECURE WITH CLIPS AND SCREWS. OTHER PANELS AVAILABLE—CONTACT FACTORY.

3 LIGHT CANDLE CLUSTER.
3 CANDELABRA SOCKETS W/PAINTED
METAL COVERS. 2 PC. PAINTED
CLUSTER BODY. 25 WATTS MAX.
PER SOCKET. (LAMPS NOT SUPPLIED)

CAST ALUMINUM SQUARE PIER BASE.



(2) 9/32" DIA. HOLES FOR 1/4" LAG SCREWS.

(2) 1/4" S.ST'L. LAG BOLTS WITH 1 1/2" ANCHOR SHIELDS SECURE FIXTURE. (CUSTOMER MUST SUPPLY (2) 1/2" DIA. X 2" DEEP HOLES ON 9 3/8" B.C.)

LANTERN WILL BE PREWIRED AND TESTED.
ALL ELECTRICAL COMPONENTS ARE UL. LISTED.
ALL MOUNTING HARDWARE IS SUPPLIED.

HEIGHT	20 1/2"
WIDTH	10" SQ.
PROJECTION	
TOP TO OUTLET	

Drawing for illustration only - scale approximate



"ABINGTON" 8100 SERIES PIER BASE LANTERN

SCALE: DATE: DWG BY: 1=4 01/25/05 ATV

B8161