

DIE CAST ALUMINUM LOOP.

CAST ALUMINUM SQUARE ROOF SECURES TO CAGE ASSEMBLY WITH 2 BRASS THUMBSCREWS. TO RELAMP, REMOVE THUMBSCREWS.


6 3/8" SQUARE

CAST ALUMINUM 4 PC. CAGE FRAME SECURELY WELDED TOGETHER TO FOR A SINGLE UNIT.

PORCELAIN MEDIUM BASE SOCKET CONCEALED BY BRASS ANODIZED ALUMINUM SLEEVE. 60 WATTS MAX. (LAMP NOT SUPPLIED).

4 CLEAR SEEDED ACRYLIC (CSA) CAGE PANELS SECURE WITH CLIPS AND SCREWS. (OTHER PANELS AVAILABLE—CONTACT FACTORY).

CAST ALUMINUM SQUARE PIER BASE.



- (2) 9/32" DIA. HOLES FOR 1/4" LAG SCREWS.
- (2) 1/4" S.ST'L. LAG BOLTS WITH 1 1/2" ANCHOR SHIELDS SECURE FIXTURE. (CUSTOMER MUST SUPPLY (2) 1/2" DIA. X 2" DEEP HOLES ON 6 3/8" B.C.)

LANTERN WILL BE PREWIRED AND TESTED. ALL ELECTRICAL COMPONENTS ARE U.L. LISTED.

ALL MOUNTING HARDWARE SUPPLIED. Drawing for illustration only — scale approximate

				T T		TITLE: "RFVFRF"
HEIGHT	13 5/8"	APPROVAL SIGNATURE:		Hanc	AVIEN	8200 SERIES
WIDTH	7" SQ.			425 E. MIDDLE ST. HA PH: (717) 632-6464 - F	NOVER PA 17331	PIER BASE LANTERN
PROJECTION] FINISH:	SCALE:	DATE:	DWG BY:	DWG. NO.
TOP TO OUTLET		OPTIONS:	1=4	01/27/05	ATV	B8261