

CAST ALUMINUM LOOP.

CAST ALUMINUM SQUARE ROOF SECURES TO CAGE WITH 2 BRASS THUMBSCREWS. TO RELAMP, REMOVE THUMBSCREWS.

9 5/8" SQUARE

4 CLEAR SEEDED ACRYLIC (CSA) CAGE PANELS SECURED WITH CLIPS AND SCREWS. OTHER PANELS AVAILABLE—CONTACT FACTORY.

3 LIGHT CANDLE CLUSTER.
3 CANDELABRA SOCKETS WITH
PAINTED METAL COVERS. 2 PC.
PAINTED CLUSTER BODY, 25 WATTS
MAX. PER SOCKET. (LAMPS NOT
SUPPLIED).

CAST ALUMINUM 4 PC. CAGE FRAME SECURELY WELDED TOGETHER TO FORM A SINGLE UNIT WITH FROG BOTTOM.

PAINTED ALUMINUM SLEEVE.

CAST ALUMINUM POST FITTER SLIPS OVER 3" O.D. POST OR TENON. (POST MUST BE ORDERED SEPARATELY).

(3) 1/4-20 S.ST'L. SET SCREWS SECURE LANTERN TO POST OR TENON.

Drawing for illustration only — scale approximate

LANTERN WILL BE PREWIRED AND TESTED.

ALL ELECTRICAL COMPONENTS ARE U.L. LISTED.

ALL MOUNTING HARDWARE IS SUPPLIED.

TITLE: "REVERE" APPROVAL SIGNATURE: HEIGHT 23 1/4" 8300 SERIES POST MOUNT WIDTH 9 5/8" 425 E. MIDDLE ST. HANOVER PA 17331 PH: (717) 632-6464 - FAX: (717) 969-2930 LANTERN FINISH: **PROJECTION** SCALE: DATE: DWG BY: DWG. NO. PANFI S: B8333 01/28/05 RSN TOP TO OUTLET OPTIONS: