



- CAST ALUMINUM LOOP.
- CAST ALUMINUM ROOF SECURES TO TOP CAGE FRAME WITH (2) 8-32 BRASS THUMBSCREWS. TO RELAMP, REMOVE THUMBSCREWS.
- CAST ALUMINUM TOP CAGE FRAME ATTACHES TO LEGS WITH 8-32 S.ST'L. MACHINE SCREWS.
- EXTRUDED ALUMINUM CAGE LEGS WITH "U" CHANNELS SECURE 3 CLEAR ACRYLIC (CA) CAGE PANELS. OTHER PANELS AVAILABLE—CONTACT FACTORY.
- CANDELABRA SOCKET WITH PAINTED METAL COVER. 25 WATTS MAX. (LAMP NOT SUPPLIED).
- PAINTED ALUMINUM STEMS.
- CAST ALUMINUM BOTTOM CAGE FRAME ATTACHES TO LEGS WITH 8-32 S.ST'L. MACHINE SCREWS.
- CAST ALUMINUM CAGE BOTTOM ATTACHES TO BOTTOM CAGE FRAME WITH 8-32 S.ST'L. MACHINE SCREWS.

LANTERN WILL BE PREWIRED AND TESTED.
 ALL ELECTRICAL COMPONENTS ARE UL. LISTED.
 MOUNTING HARDWARE SUPPLIED.

HEIGHT	20 1/8"
WIDTH	6 5/8"
PROJECTION	7 1/4"
TOP TO OUTLET	11"

Drawing for illustration only – scale approximate

	TITLE: "SALEM" 8900 SERIES WALL BRACKET LANTERN	
	SCALE: 1=4	DATE: 02/18/05

425 E. MIDDLE ST. HANOVER, PA 17331
 PH: (717) 632-6464 - FAX: (717) 669-2930

DWG. NO. B8902