



CAST ALUMINUM FINIAL.
CAST ALUMINUM SCROLL
BRACKET ARM.

CAST ALUMINUM CAP AND NECK.

PAINTED PIPE NIPPLE.

CAST ALUMINUM SQUARE ROOF
SECURES TO CAGE WITH 2
BRASS THUMBSCREWS. TO
RELAMP, REMOVE
THUMBSCREWS.

- 4 (CBG) CLEAR BEVELED GLASS CAGE PANELS SECURED WITH CLIPS AND SCREWS. OTHER PANELS AVAILABLE— CONTACT FACTORY.
- 3 LIGHT CANDLE CLUSTER.
 3 CANDELABRA SOCKETS WITH
 PAINTED METAL COVERS.
 2 PC. PAINTED CLUSTER BODY.
 25 WATT MAX. PER SOCKET.
 (LAMPS NOT SUPPLIED)

CAST ALUMINUM SQUARE CAGE WITH FROG BOTTOM.

- CAST ALUMINUM KNOB.

LANTERN IS PREWIRED AND TESTED.
ALL ELECTRICAL COMPONENTS ARE U.L. LISTED.
ALL MOUNTING HARDWARE IS SUPPLIED.

HEIGHT	22 5/8"
WIDTH	9 1/4"
PROJECTION	12 3/4"
TOP TO OUTLET	5 7/8"

Drawing for illustration only - scale approximate



9500 SERIES
WALL BRACKET
LANTERN
DWG. NO. B9572