



CAST ALUMINUM SQUARE ROOF SECURES TO CAGE ASSEMBLY WITH 2 BLACK OXIDE BRASS THUMBSCREWS. TO RELAMP, REMOVE THUMBSCREWS.

4 OPALESCENT HONEY GLASS (OHG) PANELS. (OTHER PANELS AVAILABLE—CONTACT FACTORY).

4 EXTRUDED ALUMINUM CAGE LEGS.  
WEDGE BASE SOCKET WITH 18 WATT LAMP AND 4 FEET OF #18-2 LOW VOLTAGE CABLE SUPPLIED.

CAST ALUMINUM SQUARE CAGE BOTTOM.

(4) SOCKET TYPE S.ST'L. SET SCREWS SECURE LANTERN TO POST.

4" SQ. X .125" WALL EXTRUDED ALUMINUM POST.

CONCRETE FOOTER TO BELOW LOCAL FROST LEVEL OR LOCAL CODE.

GROUND LINE

7/8" DIA. WIREWAY HOLE.

LANTERN WILL BE PREWIRED AND TESTED. ELECTRICAL COMPONENTS ARE U.L. LISTED. ALL MOUNTING HARDWARE SUPPLIED.

HEIGHT	30 1/2"
WIDTH	7" SQ.
PROJECTION	XXXXXX
TOP TO OUTLET	XXXXXX

Drawing for illustration only — scale approximate

	<small>425 E. MIDDLE ST. HANOVER PA 17331 PH: (717) 632-6464 - FAX: (717) 669-2930</small>		TITLE:	TERRALIGHT "INDIAN WELLS" LOW VOLTAGE BOLLARD
	SCALE:	DATE:	DWG BY:	DWG. NO.
1=4	10/20/08	JEK	LVW28286	