



HEIGHT	33 7/8"
WIDTH	9 1/2"
PROJECTION	
TOP TO OUTLET	

- CAST ALUMINUM BALL FINIAL.
- CAST ALUMINUM ORIENTAL ROOF SECURES TO CAGE WITH (2) 8-32 BRASS THUMBSCREWS. TO RELAMP, REMOVE BOTH THUMBSCREWS.
- 9 1/2" ACROSS POINTS
- 5 1/2" DIA. X .125" WALL X 5-3/4" LONG WHITE ACRYLIC TUBING.
- WEDGE BASE SOCKET WITH 18 WATT LAMP AND 4 FEET OF #18-2 LOW VOLTAGE CABLE.
- 2 PC. CAST ALUMINUM WELDED ORIENTAL CAGE WITH CONE BOTTOM.
- CAST ALUMINUM PIPE FITTER WITH (2) 1/4-20 S.ST'L. SET SCREWS TO SECURE FIXTURE TO GARDEN PIPE.
- 1/2" SCHEDULE 40 ALUMINUM PIPE X 24" LG. THREADED ONE END TO ATTACH TO SPIKE.
- 8 1/2" LONG LOW VOLTAGE BLACK ABS FEMALE GROUND SPIKE WITH #8 S.ST'L. SCREW.
- LOW VOLTAGE CABLE CONNECTOR TO BE USED WITH HANOVER LANTERN #10, #12, #14, OR #18 LOW VOLTAGE CABLE.

LANTERN WILL BE PREWIRED AND TESTED. ELECTRICAL COMPONENTS ARE U.L. LISTED. ALL MOUNTING HARDWARE SUPPLIED.

Drawing for illustration only - scale approximate

Hanover
LANTERN

425 E. MIDDLE ST. HANOVER PA 17331
PH: (717) 632-6464 - FAX: (717) 969-2930

TITLE: TERRALIGHT "FAR EAST" LOW VOLTAGE FIXTURE

SCALE: 1=4 DATE: 02/12/20 DWG BY: JEK

DWG. NO. LVW6324