



CAST ALUMINUM ORIENTAL FINIAL.

CAST ALUMINUM ORIENTAL ROOF SECURES TO CAGE WITH (2) 8-32 BRASS THUMBSCREWS. TO RELAMP, REMOVE BOTH THUMBSCREWS.

9" ACROSS POINTS

4" DIA. X .125" WALL X 4" LONG WHITE ACRYLIC TUBING.

WEDGE BASE SOCKET WITH 18 WATT LAMP AND 4 FEET OF #18-2 LOW VOLTAGE CABLE.

2 PC. CAST ALUMINUM WELDED ORIENTAL CAGE WITH CONE BOTTOM.

CAST ALUMINUM PIPE FITTER WITH (2) 1/4-20 S.S.T'L. SET SCREWS TO SECURE FIXTURE TO GARDEN PIPE.

1/2" SCHEDULE 40 ALUMINUM PIPE X 24" LG. THREADED ONE END TO ATTACH TO SPIKE.

8 1/2" LONG LOW VOLTAGE BLACK ABS FEMALE GROUND SPIKE WITH #8 S.S.T'L. SCREW.

LOW VOLTAGE CABLE CONNECTOR TO BE USED WITH HANOVER LANTERN #10, #12, #14, OR #18 LOW VOLTAGE CABLE.

LANTERN WILL BE PREWIRED AND TESTED. ELECTRICAL COMPONENTS ARE U.L. LISTED. ALL MOUNTING HARDWARE SUPPLIED.

Drawing for illustration only - scale approximate

HEIGHT	33 3/4"
WIDTH	9"
PROJECTION	
TOP TO OUTLET	

425 E. MIDDLE ST. HANOVER PA 17331
 PH: (717) 632-6464 - FAX: (717) 969-2930

TITLE: TERRALIGHT "LONG LIFE" LOW VOLTAGE FIXTURE

SCALE: 1=4
 DATE: 02/13/20
 DWG BY: JEK

DWG. NO. LVW6328