



- CAST ALUMINUM LOOP.
- CAST ALUMINUM SQUARE ROOF SECURED TO CAGE WITH (2) 8-32 BRASS THUMBSCREWS. TO RELAMP, REMOVE BOTH THUMBSCREWS.
- 6 7/8" ACROSS FLATS
- 4 OPAL ACRYLIC (OA) CAGE PANELS SECURE WITH CLIPS AND SCREWS. OTHER PANELS AVAILABLE-CONTACT FACTORY.
- CAST ALUMINUM CAGE ASSEMBLY WITH CONE BOTTOM.
- WEDGE BASE SOCKET WITH 18 WATT LAMP AND 4 FEET OF #18-2 LOW VOLTAGE CABLE SUPPLIED.
- CAST ALUMINUM PIPE FITTER WITH (2) 1/4-20 S.ST'L. SET SCREWS TO SECURE FIXTURE TO GARDEN PIPE.
- 1/2" SCHEDULE 40 ALUMINUM PIPE X 24" LG. THREADED ONE END TO ATTACH TO SPIKE.
- 8 1/2" LONG LOW VOLTAGE BLACK ABS FEMALE GROUND SPIKE WITH #8 S.ST'L. SCREW.
- LOW VOLTAGE CABLE CONNECTOR TO BE USED WITH HANOVER LANTERN #10, #12, #14, OR #18 LOW VOLTAGE CABLE.

LANTERN WILL BE PREWIRED AND TESTED. ELECTRICAL COMPONENTS ARE U.L. LISTED. ALL MOUNTING HARDWARE SUPPLIED.

Drawing for illustration only - scale approximate

HEIGHT	38 3/4"
WIDTH	6 7/8"
PROJECTION	
TOP TO OUTLET	

425 E. MIDDLE ST. HANOVER PA 17331
 PH: (717) 632-6464 - FAX: (717) 969-2930

TITLE: TERRALIGHT "ABINGTON" LOW VOLTAGE LANTERN

SCALE: 1=4	DATE: 02/13/20	DWG BY: JEK
------------	----------------	-------------

DWG. NO. LVW6331