



CAST ALUMINUM SQUARE ROOF SECURES TO CAGE W/(2) 8-32 BRASS THUMBSCREWS. TO RELAMP, REMOVE THUMBSCREWS.

4 OPAL ACRYLIC (OA) CAGE PANELS SECURE W/CLIPS AND SCREWS. OTHER PANELS AVAILABLE-CONTACT FACTORY.

6 3/8" ACROSS FLATS

WEDGE BASE SOCKET W/18 WATT LAMP AND 4 FEET OF #18-2 LOW VOLTAGE CABLE.

CAST ALUMINUM SQUARE OPEN BOTTOM CAGE ASSEMBLY.

CAST ALUMINUM DECORATIVE ARM WITH (2) 1/4-20 S.ST'L. SET SCREWS TO SECURE FIXTURE TO TUBING.

1/2" SCHEDULE 40 ALUMINUM PIPE X 24" LG. THREADED ONE END TO ATTACH TO SPIKE.

8 1/2" LONG LOW VOLTAGE BLACK ABS FEMALE GROUND SPIKE WITH #8 S.ST'L. SCREW.

LOW VOLTAGE CABLE CONNECTOR TO BE USED WITH HANOVER LANTERN #10, #12, #14, OR #18 LOW VOLTAGE CABLE.

LANTERN WILL BE PREWIRED AND TESTED. ELECTRICAL COMPONENTS ARE U.L. LISTED. ALL MOUNTING HARDWARE SUPPLIED.

Drawing for illustration only - scale approximate

FRONT VIEW

HEIGHT	29 1/2"
WIDTH	6 3/8"
PROJECTION	11 3/8"
TOP TO OUTLET	

425 E. MIDDLE ST. HANOVER PA 17331
 PH: (717) 632-6464 - FAX: (717) 969-2930

SCALE: 1=4 DATE: 02/13/20 DWG BY: JEK

TITLE: TERRALIGHT "REVERE" LOW VOLTAGE LANTERN
DWG. NO. LVW6332