



- CAST ALUMINUM LOOP.
- SPUN ALUMINUM ROOF CAP AND NECK ASSEMBLY.
- CAST ALUMINUM ROOF.
- FOUR CAST ALUMINUM LEGS SECURE TO ROOF AND BOTTOM WITH 8-32 STAINLESS STEEL SCREWS.
- CLEAR SEEDED GLASS GLOBE.
- ALUMINUM RING.
- 9 3/4"
- WEDGE BASE SOCKET WITH 18 WATT LAMP AND 4 FEET OF #18 LOW VOLTAGE CABLE SUPPLIED.
- CAST ALUMINUM BOTTOM.
- CAST ALUMINUM CONE BOTTOM. TO RELAMP, REMOVE (2) 8-32 BRASS THUMBSCREWS AND LIFT CAGE ASSEMBLY UP FROM CONE BOTTOM.
- CAST ALUMINUM PIPE FITTER WITH (2) 1/4-20 STAINLESS STEEL SET SCREWS TO SECURE FIXTURE TO GARDEN PIPE.
- 1/2" SCHEDULE 40 ALUMINUM PIPE X 24" LONG THREADED ONE END TO ATTACH TO SPIKE.
- 8 1/2" LONG LOW VOLTAGE BLACK ABS FEMALE GROUND SPIKE WITH #8 STAINLESS STEEL SCREW.
- LOW VOLTAGE CABLE CONNECTOR TO BE USED WITH HANOVER LANTERN #10, #12, #14, OR #18 LOW VOLTAGE CABLE.

LANTERN WILL BE PREWIRED AND TESTED. ELECTRICAL COMPONENTS ARE U.L. LISTED. ALL MOUNTING HARDWARE IS SUPPLIED.

Drawing for illustration only - scale approximate

HEIGHT	40 1/4"
WIDTH	9 3/4"
PROJECTION	
TOP TO OUTLET	

Hanover
LANTERN

425 E. MIDDLE ST. HANOVER PA 17331
PH: (717) 632-6464 - FAX: (717) 969-2930

SCALE: 1=4 DATE: 02/17/20 DWG BY: RSN

TITLE: TERRALIGHT "BRIDGEWATER" LOW VOLTAGE LANTERN

DWG. NO. LVW6368