Canfield Patio 52" Fan Satin Black

310192SBK (Satin Black)

| Project Name: | |
|---------------|--|
| Location: | |
| Type: | |
| Qty: | |
| Comments: | |
| | |



| Airflow | | |
|------------|------|--|
| CFM (High) | 5481 | |
| CFM (Low) | 1588 | |
| RPM (High) | 185 | |
| RPM (Low) | 58 | |

| Certifications/Qualifications | | |
|-------------------------------|-------------------|--|
| Location Rating | CSA UL Listed Wet | |
| Title 20 Compliant | Yes | |

| Dimensions | |
|----------------|-----------------|
| Base Backplate | 6.25 DIA |
| Downrod 1 | 1.00 OD X 4.00" |
| Weight | 24.20 LBS |
| Height | 13.25" |
| Width | 52.00" |

www.kichler.com/warranty

| Electrical | |
|-------------|--------------|
| Amps (High) | 0.59 |
| Amps (Low) | 0.22 |
| Motor Size | 172MM X 20MM |
| Motor Tupe | AC |

| Mounting/Installation | | |
|-----------------------------------|--------------------------------|--|
| Dual Mount | Yes | |
| Minimum Distance from Fa Floor | n to 7feet | |
| Interior/Exterior | Exterior | |
| Lead Wire Length | 78 | |
| Low Ceiling Adaptable | Yes, With Optional Flush Mount | |
| Mounting Weight | 24.20 LBS | |

| Primary Lamping | | |
|------------------|----------|--|
| Downlight Option | Optional | |
| Watts (High) | 71 | |
| Watts (Low) | 9 | |

| Product/Ordering Information | |
|------------------------------|-------------|
| SKU | 310192SBK |
| Finish | Black |
| Style | Traditional |

783927366663

| Specifications | |
|------------------|----------------|
| | |
| Blade Finish 1 | SATIN BLACK |
| Blade Finish 2 | NON-REVERSIBLE |
| Blade Material | ABS |
| Blade Pitch | 14 |
| Blades Included | Yes |
| Blade Sweep | 52 |
| Material | STEEL |
| Max Stem Tilt | 30 Degrees |
| Number of Blades | |

Additional Finishes



UPC

Satin Black



Kichler 7711 East Pleasant Valley Road Cleveland, Ohio 44131-8010 Toll free: 866.558.5706 or kichler.com

Notes:
1) Information provided is subject to change without notice.
All values are design or typical values when measured under laboratory conditions.
2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

