

Rely™ 36"x42" Shower Base **K-8647**

GREENGUARD FROGUCT CERTILIO FOR LOW COMBINAL EMISSIONS ULCOM/CG U. 2339

Features

- Center drain.
- Low-threshold assures ease of exit and entry of the shower space.
- Water containment bead along the step over threshold provides optimum barrier to eliminate water escaping from the shower.
- Textured bottom surface.
- One-piece construction.
- Compliments traditional and contemporary bathroom designs.
- Coordinates with Choreograph™ walls.

Material

Acrylic.

Installation

- Alcove.
- 3-side integral flange.



Codes/Standards

CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662 Greenguard UL 2818 - Gold

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Color/Finishes


Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	NY	Dune
	95	Ice™ Grey
	G9	Sandbar









Technical Information

All product dimensions are nominal.

Installation:

3-Wall Alcove

Drain location: Center

Weight: 48 lbs (21.8 kg)
Threshold height: 2-15/16" (74 mm)

Notes

Measure your actual product for rough-in details. Install this product according to the installation instructions.

Subfloor must be within 1/2" (13 mm) of level.

This receptor has a front lip. This should be taken into account when installing a shower door.

