

# Kingston™

toilet tank K-25100

#### **Features**

- Ideal for commercial installations.
- 1.28 gallons per flush (gpf).
- Durable metal left-hand Polished Chrome trip lever included.
- Combines with a K-25076 or K-25076-SS bowl to create a complete K-25077 or K-25077-SS Kingston two-piece toilet.

## **Technology**


- Single-flush gravity uses the force of gravity and a precision-engineered tank, bowl and trapway to create a strong siphon during flushing.
- Class Five® flushing technology offers virtually plug-free performance and rinsing power for a clean bowl.
- Class Five® canister allows water to flow out of the tank from all sides (360 degrees), increasing the power and effectiveness of the flush.
- Flush valve's 3:2 ratio harnesses the natural force of gravity and optimizes flush performance.
- Durable canister design has 90% less exposed seal material than a 3" flapper, for virtually leak-free performance.

#### Installation

- Three-bolt quick-connect installation.
- Supply line not included.

## Components

Additional included component/s: Tank Cover, Trip Lever, and Hardware kit.



## Codes/Standards ASME A112.19.2/CSA B45.1

**KOHLER® One-Year Limited Warranty** See website for detailed warranty information.

## **Available Color/Finishes**

Color tiles intended for reference only.

**Color Code Description** 

0 White





Kingston™ toilet tank K-25100

No image available. This product is a component and not intended to be a standalone installation.

### **Technical Information**

All product dimensions are nominal.

Toilet type: Two-piece, Floor-mount

Waste Outlet: Floor

Flush type: Gravity siphon jet

Water Consumption

Full: 1.28 gpf (4.8 lpf)

#### **Notes**

Install this product according to the installation instructions.

Install this product according to the installation instructions.

