### **NELOCAC**

ELO and ELO+ LED Surface Mount Luminaire

Source: 12W to 24W LED 700lm to 1700lm

# Type Project Catalog No. Notes

#### PRODUCT DESCRIPTION

ELO family of LED luminaires are a thin  $\frac{1}{2}$ " surface mounted luminaire with dedicated color temperature. Luminaire is available in 6", 8" or 11" sizes and mounts easily over a standard or fire rated junction boxes. The ELO family has two options: The standard ELO fixture, which is 80 CRI and only available in a white finish, and the upgraded ELO+ fixture, which meets CA JA8-2019 at 90 CRI and has interchangeable trims to achieve different finishes.

#### **FEATURES**

- · Dedicated color temperatures at 80 CRI (ELO) or 90 CRI (ELO+)
- Surface mounted or retrofit into existing recessed housings with torsion spring kit (ordered separately)
- · Available in three sizes (6", 8" or 11")
- · Dimmable with Triac or ELV dimmers
- · ELO+ Series includes an integral magnet allows optional finish ring to attach seamlessly\*
- · 5-year limited warranty

#### **SPECIFICATION**

**Construction:** Surface mounted luminaire includes integral driver. ELO+ luminaires include an integral magnet for decorative rings in black, brushed nickel, chrome or matte powder white finish (ordered separately).

**Mounting:** Steel bracket can be used to surface mount on junction box. Optional torsion springs are available for retrofitting 5" or 6" recessed housings.

#### ELECTRICAL Input Voltage: 120V

Lumens / Wattage: 6" = 700lm / 12W; 8" = 1100lm / 18W; 11" = 1700lm / 24W

Color Temperature: 2700K, 3000K, 3500K, 4000K or 5000K

Color Rendering Index: 80 or 90Operating Temperature:  $0\text{-}45^{\circ}\text{C}$ 

Dimming: Triac or ELV

<u>Click Here</u> or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

#### **ACCESSORIES**

**Decorative Rings:** ELO+ Series includes an integral magnet to mount optional decorative rings seamlessly. Finishes include black, brushed nickel, chrome or matte powder white in 6", 8" or 11" sizes.

\* Optional decorative rings are held in place with integral magnets. Installations that might have heavy vibrations should be tested. **NLOCAC-681IRECKIT:** ELO & ELO+ Series can be mounted to a 5" or 6" recessed housings with torsion spring brackets using optional torsion spring kit.

#### LABELS AND LISTINGS

- · cETLus Listed for Damp Location
- ENERGY STAR® certified
- FCC certified
- 5-Year Limited Warranty
- · Certified to the high efficacy requirements of California Title 24 JA8-2019 (ELO+ only)
- · Suitable for use in closets when installed in accordance to NEC Section 410.16 (A)(1) and 410.16 (C)(1)





















Performance Data					
Part Number	Lumens	CCT	CRI		
NELOCAC-6RP940W	729Im	4000K	90 CRI		
NELOCAC-6R30W	779Im	3000K	80 CRI		
NELOCAC-8RP940W	1168Im	4000K	90 CRI		
NELOCAC-8R30W	1191lm	3000K	80 CRI		
NELOCAC-11RP940W	1712lm	4000K	90 CRI		
NELOCAC-11R30W	1720lm	3000K	80 CRI		

Delivered lumens will vary depending on CCT

#### **PRODUCT IMAGES & DIMENSIONS**





11" ELO

**ELO and ELO+ LED Surface Mount Luminaire** 

	Luminaire Size	Color Temperature / CRI	Finish
	NELOCAC-6RP = 6" ELO+	<b>927</b> = 2700K / 90 CRI	<b>W</b> = White
ELO+	NELOCAC-8RP = 8" ELO+	930 = 3000K / 90 CRI	
	NELOCAC-11RP = 11" ELO+	<b>935</b> = 3500K / 90 CRI	
н		940 = 4000K / 90 CRI	
		<b>950</b> = 5000K / 90 CRI	
	NELOCAC-6R = 6" ELO	<b>30</b> = 3000K / 80 CRI	<b>W</b> = White
믑	NELOCAC-8R = 8" ELO		
	NELOCAC-11R = 11" FLO		

**Optional Accessories** 

Description

NLOCAC-6R = 6" Ring for ELO+ only NLOCAC-8R = 8" Ring for ELO+ only NLOCAC-11R = 11" Ring for ELO+ only Decorative Ring Finish **B** = Black **BN** = Brushed Nickel

CH = Chrome MPW = Matte Powder White

NLOCAC-6811 RECKIT = Retrofit Kit

Example: NELOCAC-8RP930W = 8" ELO+ LED Surface Mount Luminaire, 3000K / 90 CRI, White finish



## **NELOCAC**

# ELO and ELO+ LED Surface Mount Accessories

Type
Project
Catalog No.
Notes









Decorative Ring for ELO+

NLOCAC-6RB 6° Black
NLOCAC-8RB 8° Black
NLOCAC-11RB 11° Black
Seamlessly attaches to luminaire.

Decorative Ring for ELO+

NLOCAC-6RBN 6" Brushed Nickel
NLOCAC-8RBN 8" Black
NLOCAC-1IRBN 11" Black
Seamlessly attaches to luminaire.
Compatible with ELO+ only.

Decorative Ring for ELO+

NLOCAC-6RCH 6" Chrome
NLOCAC-8RCH 8" Chrome
NLOCAC-1IRCH 1" Chrome
Seamlessly attaches to luminaire.
Compatible with EL0+ only.

Decorative Ring for ELO+

NLOCAC-6RMPW 6" Matte Powder White NLOCAC-8RMPW 8" Matte Powder White NLOCAC-1IRMPW 11" Matte Powder White Seamlessly attaches to luminaire. Compatible with ELO+ only.



Retrofit Kit

## NLOCAC-6811RECKIT

Allows luminaires to mount over 5" or 6" recessed housings with torsion spring brackets.