

NT-5020

5" Specular Reflector with White Metal Ring

FEATURES

Trim: Precision spun high grade reflector and baffle with deep grooves to reduce aperture glare.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

LAMP

75W BR/PAR30 Maximum (NFBIC-5INCATA; NHIC-501QAT; NHRIC-504QAT; NH-501Q; NHR-504Q)

LABELS AND LISTINGS

· cULus Listed for Damp Location when used with compatible housing



Type _____

Project _____

Catalog No. _____

Notes _____

PRODUCT IMAGES AND DIMENSIONS




NT-5020B



NT-5020W



NT-5020C



5" Specular Reflector with White Metal Ring

Catalog No. _____

NT-5020B = Specular Black Reflector with White Metal Ring

NT-5020C = Specular Clear Reflector with White Metal Ring

NT-5020W = Specular White Reflector with White Metal Ring

Compatible Housings

Catalog No. _____

NHIC-501QAT = 5" IC Air-Tight New Construction / 75W max

NHRIC-504QAT = 5" IC Air-Tight Remodel / 75W max

NH-501Q = 5" Non-IC New Construction / 75W max

NHR-504Q = 5" Non-IC Remodel / 75W max

NFBIC-5INCATA = 5" IC Air-Tight Fire Rated New Construction / 75W max

Example: **NT-5020W** = 5" Specular White Reflector with White Metal Ring