

BILLOWS

 Ceiling mounted • Dry location listed **PROGRESS LED**

Description:

The 52" Billows ceiling fan features an LED light kit with white opal glass shade and five reversible blades. With a sophisticated and traditional design, the Billows offers both form and function with two energy efficient 10W MaxLite LED lamps, featuring a 3000K color temperature.

Specifications:

- Brushed Nickel (-09) (plated)
- Steel construction
- Frosted bowl
- 52" 5 Blade Fan with LED light
- Oversized, textured die cast hanger ball reduces noise and wobble vibrations
- Mounting hardware is included
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- 54 in of wire supplied
- Silver/Whitewashed Grey reversible blades, plywood construction
- with Maple fob
- Chrome pull chain 13.5 degree blade pitch
- A 3/4" x 4-1/2" downrod is included. Longer accessory downrods can be ordered separately. Triple capacitor speed control, manual reverse control
- Airflow: 4682 CFM*
- Energy consumption: 59 watts (excluding lights)*
- Airflow efficiency: 79 cfm/watt*
- * Fan on a downrod

Performance:

Number of Modules	2
Input Power	10w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	800/80 (LM-79) per module
CCT	3000 K
CRI	90+
Life (hours)	(L70/TM-21)
EMI/RFI	FCC Title 47, Part 15 Class B
Min. Start Temp	-30°C
Max. Operating Temp	30°C
Warranty	Limited Lifetime warranty
Labels	UL Dry location listed

P2552-09

Images:



Dimensions:

Diameter: 52"
Height: 17-1/2"

ENERGYGUIDE

Estimated
Yearly Energy Cost

\$10

\$3

\$34

Cost Range of Similar Models (19" – 84")

• Based on 12 cents per kWh and 6.4 hours use per day
 • Your cost depends on rates and use
 • Energy Use: 37 Watts

Airflow

3369

Cubic Feet Per Minute

• The higher the airflow, the more air the fan will move
 • Airflow Efficiency: 92 Cubic Feet Per Minute Per Watt

All estimates based on typical use, excluding lights ftc.gov/energy