

#### Project:

Fixture Type: Location:

Contact:

**LED** Pendant

Ceiling cord mounted • Dry location listed PROGRESS LED

Images:



# P5176-2030K9

One-light cord-hung pendant with an LED source that is neatly tucked inside a frosted acrylic shade. A light commercial pendant ideal for restaurants, bar and hotel applications.

## **Specifications:**

**Description:** 

- · Antique Bronze (-20) (painted)
- Steel Construction
- · White polystyrene shade, White acrylic diffuser
- LED Module is replaceable (part # 93054049)
- Light commercial LED pendant.
- Frosted acrylic shade.
- $\cdot$   $\,$  Ideal for restaurants, bar and hotel applications.
- 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 10 feet of wire supplied
- ENERGY STAR® qualified

#### **Performance:**

Number of Modules	1	Dimen
Input Power	9w	Diamete Height: Overall Glass Width: <u>2</u> Length: Glass 2 Width: <u>2</u> Length: Height:
Input Voltage	120 V	
Input Frequency	60 Hz	
Lumens/LPW (Source)	623/69.2 (LM-82)	
Lumens/LPW (Delivered)	405/54 (LM-79)	
ССТ	3000 К	
CRI	90 CRI	
Life (hours)	60,000 (L70/TM-21)	
FCC	Meets FCC Title 47, Part 15 Class B	
Min. Start Temp	-30 °C	
Max. Operating Temp	30 °C	
Warranty	5 year warranty	
Labels	cCSAus Dry location listed	
	ENERGY STAR <sup>®</sup> qualified	



#### **Dimensions:**

Diameter: 5-7/8" Height: 8-5/8" Overall Ht. W/Cord: 130"

Glass Width: 5-13/16" Length: 5-13/16" Height: 6-7/16" Glass 2 Width: 2-7/8" Length: 2-7/8" Height: 0-13/16"



# LED Pendant



#### **Dimming Notes:**

P5176 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

### **Dimming Controls**

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.