SATCO" NUVO

Project Name

Location

Prepared By



SATCO S39798

40W/LED/HID/MB-G3/27K/100-277V

Notes

General Status Active Watts 40 Incandescent Equivalent 300 Fluorescent Equivalent 65 HID Equivalent 175 Volts 100V-277V Shape Corncob Base Mogul Extended ANSI Base EX39 Finish Clear CCT (Kelvin) 2700 Temperature Warm White CRI 80 Lumens 5120 Beam Spread 120;150;260 Dimmable Non-Dimmable Hours Rated 50000 Lamp Type LED HID LED Technology Width: 8.00 in. Depth: 8.00 in. Min Compartment Size Height: 11.00 in. Electrical

Licothoan	
Operating Frequency	50/60 Hz
Power Factor	>0.9
Surge Protection	Built-in surge protection - 4KV
THD	<20%
Operating Temperature	-20C (-4F) to a maximum of +65C (+149F)

PhysicalMOL7.24MOD3.35Housing ColorWhitePhotocellOptional Add-OnWeight (lb.)1.85

Additional Information

Additional Info	PIR Sensor available as an accessory
Enclosure Rating	Enclosed Rated Lamp
Rated For Enclosed Fixture	Yes
IP Rating	IP64
Specification Note	Closed 260 deg; Partial 150 deg; Open 120 deg
Warranty	5 Year Limited - Hi-Pro
Compliance	
Safety Listing	cULus Classified
Location Rating	Damp

in f 7 0

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: <u>https://www.satco.com/</u>

Energy Star	No
DLC Approved	Yes
DLC ID	PLQ3VZ94GZN0
CEC Status	Lawful for sale in California
RoHS Compliant	Yes
SDS Sheet	LED_Lamp

For More Information Visit: <u>https://www.satco.com/</u>

