

The scale and classic profile of the Bowman pendant make a strong design statement in both residential and commercial outdoor environments. Featuring a spun aluminum body and subtle diffuser, the Bowman pendant houses a powerful LED light source designed to deliver softly diffused down lighting for controlled and distinctive illumination.

Outstanding protection against the elements:

- Marine-grade powder coat finishes
- Stainless Steel mounting hardware
- Impact-resistant, UV stabilized lensing
- IP-65 Rated

Adjustable distance from ceiling

SPECIFICATIONS

DELIVERED LUMENS	1320
WATTS	21
VOLTAGE	Universal 120-277V
DIMMING	0-10, ELV, TRIAC
LIGHT DISTRIBUTION	Symmetric
MOUNTING OPTIONS	Ceiling
ADJUSTABILITY	Adjustable stem length (3", 6" and 12"). Integrated ball joint that accommodates sloped ceiling up to 45°.
CCT	2700K, 3000K or 4000K
CRI	90+
COLOR BINNING	3 Step
BUG RATING	B1-U2-G1
DARK SKY	Non-compliant
WET LISTED	IP65
GENERAL LISTING	ETL
CALIFORNIA TITLE 24	Can be used to comply with CEC 2016 Title 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required.
START TEMP	-30°C
FIELD SERVICEABLE LED	Yes
CONSTRUCTION	Aluminum
HARDWARE	Stainless Steel
FINISH	Marine Grade Powder Coat
LED LIFETIME	L70; 70,000 Hours
WARRANTY*	5 Years

^{*} Visit techlighting.com for specific warranty limitations and details.






BOWMAN 12 PENDANT shown in bronze

ORDERING INFORMATION

700OPBOW	CRI /	CRI / CCT		WIDTH		FINISH		VOLTAGE	
	930	90 CRI, 2700K 90 CRI, 3000K 90 CRI, 4000K	12	12"	Н	BRONZE CHARCOAL BLACK	UNV	120V-277V	
RIGID STEM ONLY (A	DJUSTAE	BLE 3", 6" AND 12"	LENG1	THS)					




Bowman Pendant

PHOTOMETRICS*

*For latest photometrics, please visit www. techlighting.com/OUTDOOR

BOWMAN 12 PENDANT

Total Lumen Output: 1320
Total Power: 21
Luminaire Efficacy: 63
Color Temp: 4000K
CRI: 90+
BUG Rating: B1-U2-G1



PROJECT INFO

FIXTURE TYPE & QUANTITY JOB NAME & INFO NOTES



GENERATION BRANDS 7400 Linder Avenue, Skokie, Illinois 60077 T 847.410.4400 F 847.410.4500