


LUCIO – model: LED 6022

W Track System Luminaires

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Museum-quality LED luminaire with high performance optics.

FEATURES

- Recessed driver hidden in track
- Accommodates up to 1 lens and 1 glare control accessory
- 365° horizontal aiming and 90° indexed vertical aiming
- Integral selector to choose between independently controllable track circuits
- CBCP intensive ultra spot, 6022U
- Asymmetrical beam distribution, 6022A
- 50,000 rated life
- 5 year warranty

SPECIFICATIONS

- Construction:** Die-cast aluminum body with regressed driver.
- Input:** 120 VAC, 277VAC 50/60Hz
- Power:** 22W
- Light Source:** High output COB LED
- Dimming:** 100%-5% Electronic Low Voltage (ELV), TRIAC
- Standards:** UL & cUL Dry Location Listed, Title 24 JA8-2019 Compliant
- Finish:** Electrostatically powder coated White, Black, Platinum

Track	Model	Beam	Lumens @ 830	CBCP @ 830	Color Temp	CRI	Finish
WTK 120V WHK 277V	6022	U 8°	1440	35,370	827 2700K	85	BK Black PT Platinum WT White
		S 12°	1690	15,235	830 3000K	85	
		N 20°	1675	8295	835 3500K	85	
		F 35°	1650	3730	840 4000K	85	
		A ASY	1755	N/A	927 2700K	90	
					930 3000K	90	

WTK-6022 - -

Example: **WTK-6022F-827-PT**

REPLACEMENT OPTICS

'U' and 'A' are dedicated optics

12°	REF-84BL10-S
20°	REF-84BL10-N
35°	REF-84BL10-F

Accommodates one lens accessory and one glare control accessory. 'U' and 'A' beam fixtures accept one glare control accessory.

LENS ACCESSORIES

Amber	LENS-25-AMB	Yellow	LENS-25-YEL
Blue	LENS-25-BLU	Frosted	LENS-25-FR
Green	LENS-25-GRN	Spread	LENS-25-SPR
Red	LENS-25-RED	Beam Elongating	LENS-25-BEL

GLARE CONTROL ACCESSORIES

Cross Louver	LENS-25P-CRL-BK LENS-25P-CRL-PT LENS-25P-CRL-WT	Snoot	LENS-25-SNOOT-BK LENS-25-SNOOT-PT LENS-25-SNOOT-WT
Honey Comb Louver	LENS-25-HCL		

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

FIXTURE PERFORMANCE

Model #	Beam	Color Temp	Lumens	CBCP	CRI	Model #	Beam	Color Temp	Lumens	CBCP	CRI
WTK-6022U-827 WHK-6022U-827	8°	2700K	1395	33,925	85	WTK-6022F-827 WHK-6022F-827	35°	2700K	1585	3,595	85
WTK-6022U-830 WHK-6022U-830		3000K	1440	35,370	85	WTK-6022F-830 WHK-6022F-830		3000K	1650	3,730	85
WTK-6022U-835 WHK-6022U-835		3500K	1520	35,535	85	WTK-6022F-835 WHK-6022F-835		3500K	1660	3,730	85
WTK-6022U-840 WHK-6022U-840		4000K	1550	35,930	85	WTK-6022F-840 WHK-6022F-840		4000K	1825	4,120	85
WTK-6022U-927 WHK-6022U-927		2700K	1105	26,685	90	WTK-6022F-927 WHK-6022F-927		2700K	1365	3,080	90
WTK-6022U-930 WHK-6022U-930		3000K	1215	29,490	90	WTK-6022F-930 WHK-6022F-930		3000K	1385	3,115	90
WTK-6022S-827 WHK-6022S-827	12°	2700K	1625	14,675	85	WTK-6022A-827 WHK-6022A-827	ASY	2700K	1585	N/A	85
WTK-6022S-830 WHK-6022S-830		3000K	1690	15,235	85	WTK-6022A-830 WHK-6022A-830		3000K	1755		85
WTK-6022S-835 WHK-6022S-835		3500K	1680	15,055	85	WTK-6022A-835 WHK-6022A-835		3500K	1840		85
WTK-6022S-840 WHK-6022S-840		4000K	1890	17,030	85	WTK-6022A-840 WHK-6022A-840		4000K	1765		85
WTK-6022S-927 WHK-6022S-927		2700K	1405	12,720	90	WTK-6022A-927 WHK-6022A-927		2700K	1455		90
WTK-6022S-930 WHK-6022S-930		3000K	1415	12,845	90	WTK-6022A-930 WHK-6022A-930		3000K	1430		90
WTK-6022N-827 WHK-6022N-827	20°	2700K	1605	7,980	85						
WTK-6022N-830 WHK-6022N-830		3000K	1675	8,295	85						
WTK-6022N-835 WHK-6022N-835		3500K	1670	8,320	85						
WTK-6022N-840 WHK-6022N-840		4000K	1865	9,115	85						
WTK-6022N-927 WHK-6022N-927		2700K	1380	6,790	90						
WTK-6022N-930 WHK-6022N-930		3000K	1400	7,050	90						