

TEMPT

 Ceiling mounted • Dry location listed **PROGRESS LED**

Description:

This five-blade 52" Tempt ceiling fan features a clear glass shade. A remote with batteries is included. Tempt features a dual mount system to offer greater flexibility when installing. The 17W dimmable, 3000K LED module provides energy- and cost-savings benefits to the homeowner. Can be used to comply with California Title 20.

Specifications:

- Antique Bronze (-20) (Painted)
- Steel construction
- Clear double cut prismatic glass Bowl
- The light kit contains a clear double cut prismatic glass shade and contains a 17W dimmable 3000K LED module with 90CRI and 1400 lumens
- Features reversible Medium Cherry/American Walnut blades and an Antique Bronze finish
- A hand held remote control with fan speed control and full range light dimming is included and comes with a convenient wall bracket for storage
- The five-blade Tempt fan features a dual mount system to offer greater flexibility when installing. The fan can be installed on a flat or sloped ceiling
- Indoor ceiling fan ideal for use in great rooms, living rooms, bedrooms and bonus rooms
- Ideal for Transitional interiors
- Reversible motor for year round comfort allows you to choose either a down draft (summer) or an up draft (winter)
- As a general rule of thumb, lighting experts suggest this fan is ideal in a room size that ranges from 226- to 400-square feet
- A 3/4" x 4-1/2" downrod is included. Longer accessory downrods can be ordered separately
- UL dry location listed for indoor use
- Can be used to comply with California Title 20.
- High Speed Energy Information: Airflow- 4314 cfm, Energy consumption- 62 watts (excluding lights), Airflow efficiency- 78 cfm/watt
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 80" of wire supplied
- Medium Cherry/American Walnut reversible blades, plywood construction
- 12 degree blade pitch
- Full Function Remote Included
- Meets California Title 24 JA8-2016

Performance:

Number of Modules	1
Input Power	17w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1386/77 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50,000 (L70/TM-21)
EMI/RFI	Title 20
Min. Start Temp	-10 °C
Max. Operating Temp	40 °C
Warranty	Limited Lifetime warranty
Labels	UL Dry location listed
	Meets California Title 24 JA8-2016

 For more information visit our website: www.progresslighting.com

P2578-2030K

Images:



Dimensions:

 Diameter: 52"
 Height: 14-3/4"

ENERGYGUIDE

Estimated
Yearly Energy Cost

\$11

\$3
\$34

Cost Range of Similar Models (19" – 84")

- Based on 12 cents per kWh and 6.4 hours use per day
- **Your cost depends on rates and use**
- Energy Use: 41 Watts

Airflow

3,198

Cubic Feet Per Minute

- The higher the airflow, the more air the fan will move
- Airflow Efficiency: 78 Cubic Feet Per Minute Per Watt

All estimates based on typical use, excluding lights ftc.gov/energy

P2578-2030K

Dimming Notes:

P2578 is designed to be compatible with many controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

"Lutron - NTEVL-300

Lutron - DVELV-300P

Lutron - Caseta Wireless

Leviton – 6672

Leviton – 6674

Lutron - AYCL-153P

Lutron - AYLV-600P

Lutron - MAELV-601

Leviton - AWRMG-EAW"

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.