

Medium Wall Lantern

Wall mounted • Wet location listed



Description:

The one-light medium LED outdoor wall lantern from the District Collection features metal shade that offers an industrial-inspired design. The versatile vintage form can be used in indoor and outdoor applications. Metallic Gray finish.

Specifications:

- Metallic Gray (-82) (painted)
- Aluminum Construction
- Metallic Gray, painted white inside aluminum shade, White acrylic Diffuser
- LED Module is replaceable (part # 93054049)
- Versatile vintage form.
- Metal shade that offers an industrial-inspired design.
- Can be used in both indoor and outdoor applications.
- 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- Meets California Title 24 high efficacy requirements for outdoor use only

Performance:

Number of Modules	1
Input Power	9w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	623/69.2 (LM-82)
Lumens/LPW (Delivered)	561/71.9 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Wet location listed ENERGY STAR® qualified Meets California Title 24 high efficacy requirements for outdoor use only

P5622-8230K9

Images:



Dimensions:

Width: 8"
Depth: 10-1/4"
Height: 8-1/4"
H/CTR: 4-1/8"

Glass
Width: 8-1/16"
Length: 8-1/16"
Height: 5-7/8"
Glass 2
Width: 2-7/8"
Length: 2-7/8"
Height: 0-13/16"

Photometrics:

P5622-8230K9

ELECTRICAL DATA	P5622-8230K9
Input Voltage	120 V
Input Frequency	60 Hz
Input Current	0.075 A
Input Power	9
Power Factor	Greater than 0.90
THD	<20%
FCC	Meets FCC Title 47, Part 15 Class B
Operating Temperature	-30 °C to 30 °C
Dimming	Yes*

*See Dimming Notes for more information

P5622-8230K9


LED Light Engine: 3000 K 90 CRI
 System Wattage: 9
 Fixture delivered lumens: 561
 Fixture Efficacy: 71.9
 Spacing Criteria: 1.3

CANDELA DISTRIBUTION

DEG	CANDELA	LUMENS
0	258	
5	261	25
15	255	72
25	238	110
35	217	135
45	177	126
55	57	53
65	21	21
75	12	13
85	6	6
90	0	

ZONAL LUMEN SUMMARY

ZONE	LUMENS	%FIXT
0-30	207	37.0
0-40	342	61.1
0-60	521	93.0
0-90	561	100.0
90-180	0	0.0
0-180	561	100.0



P5622-8230K9**Dimming Notes:**

P5622 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vieri VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.