

CUBE ARCHITECTURAL DC-PD05

LED Pendant Mounts

WAC LIGHTING

Responsible Lighting®



24"

Extension rod for additional length up to 96"

DS-PDX24

Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cubical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

FEATURES

- High performance exterior rated LED pendant
- Includes 45° swivel canopy and 2 field cuttable 24" rods
- Solid aluminum construction
- 39° visual cutoff angle for glare control
- 5 year warranty
- JA8-2016 Title 24 (Labeled with *)

SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 5% (120V only)
0-10V: 100% - 1% (120-277V)
- Light Source:** High output 3 Step Mac Adam Ellipse COB
Rated life of 60,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, UL & cUL wet location listed

ORDERING NUMBER

Diameter	Watt	Beam	Beam Angle	Color	Temp	CRI	Lumen	CBCP	Efficacy (Lm/W)	Light Distribution	Finish
<p>DC-PD05</p>	5" 27W	S Spot	18°	927*	2700K	90	1680	8526	62		BK Black WT White BZ Bronze GH Graphite
				827	2700K	85	1800	9151	67		
				930*	3000K	90	1700	8639	63		
				830	3000K	85	1995	10126	74		
				835	3500K	85	2190	11118	81		
	840	4000K	85	2260	11483	84					
	N Narrow	25°	927*	2700K	90	1730	5513	64			
			827	2700K	85	1855	5918	69			
			930*	3000K	90	1750	5587	65			
			830	3000K	85	2055	6548	76			
			835	3500K	85	2255	7190	84			
	840	4000K	85	2330	7426	86					
	F Flood	33°	927*	2700K	90	1725	4246	64			
			827	2700K	85	1850	4557	69			
			930*	3000K	90	1745	4302	65			
830			3000K	85	2045	5043	73				
835			3500K	85	2245	5537	83				
840	4000K	85	2320	5719	86						

DC-PD05- _____ - _____

Example: **DC-PD05-S930-GH**




wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

MOUNTING ACCESSORIES

	<i>Extension Rod</i>	DS-PDX24	<i>One 24" extension rod for DC-PDSK Can be field cut</i>	Finish	
				BK <i>Black</i>	
				WT <i>White</i>	
				BZ <i>Bronze</i>	
				GH <i>Graphite</i>	

Example: **DC-PDX24-WT**

CUBE ARCHITECTURAL DC-PD06

LED Pendant Mounts

WAC LIGHTING

Responsible Lighting®



24"

Extension rod for additional length up to 96"

DS-PDX24

Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cubical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

FEATURES

- High performance exterior rated LED pendant
- Includes 45° swivel canopy and 2 field cuttable 24" rods
- Solid aluminum construction
- 38° visual cutoff angle for glare control
- 5 year warranty
- JA8-2016 Title 24 (Labeled with *)

SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 5% (120V only)
0-10V: 100% - 1% (120-277V)
- Light Source:** High output 3 Step Mac Adam Ellipse COB
Rated life of 70,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, UL & cUL wet location listed

ORDERING NUMBER

Diameter	Watt	Beam	Beam Angle	Color Temp	CRI	Lumen	CBCP	Efficacy (Lm/W)	Light Distribution	Finish
<p>DC-PD06</p>	6" 36W	S Spot	19°	927* 2700K	90	1875	8911	51		BK Black WT White BZ Bronze GH Graphite
				827 2700K	85	2400	11392	65		
				930* 3000K	90	2000	9500	54		
				830 3000K	85	2170	10317	59		
				835 3500K	85	2500	11884	68		
				840 4000K	85	2450	11639	66		
	6" 36W	N Narrow	30°	927* 2700K	90	1830	4642	49		
				827 2700K	85	2340	5935	63		
				930* 3000K	90	1950	4949	53		
				830 3000K	85	2120	5374	57		
				835 3500K	85	2440	6191	66		
				840 4000K	85	2390	6063	65		
	6" 36W	F Flood	40°	927* 2700K	90	1840	3310	50		
				827 2700K	85	2355	4231	64		
				930* 3000K	90	1965	3528	53		
				830 3000K	85	2130	3832	58		
				835 3500K	85	2455	4414	66		
				840 4000K	85	2405	4323	65		

DC-PD06-_____ - _____

Example: **DC-PD06-S930-GH**





wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

MOUNTING ACCESSORIES

 <p>Extension Rod</p>	DS-PDX24	<i>One 24" extension rod for DC-PDSK Can be field cut</i>	Finish												
			<table><tr><td>BK</td><td>Black</td><td></td></tr><tr><td>WT</td><td>White</td><td></td></tr><tr><td>BZ</td><td>Bronze</td><td></td></tr><tr><td>GH</td><td>Graphite</td><td></td></tr></table>	BK	Black		WT	White		BZ	Bronze		GH	Graphite	
BK	Black														
WT	White														
BZ	Bronze														
GH	Graphite														

Example: **DC-PDX24-WT**